

NOW AVAILABLE IN 5/8" SIZE!



# SUPER SWAGED

## Winch Lines


### FEATURES & BENEFITS



- **STRONGER** - Compact design allows for up to 26% greater strength than standard winch lines of the same diameter
- **MORE DURABLE** - Due to the swaging process the outer wires have a larger surface area than that of standard winch lines providing better resistance to abrasion, pig tailing & kinking
- **RESISTANT TO DRUM CRUSHING** - Because the winch line is already compacted during the swaging process there is less space within the rope to compact if exposed to crushing
- **CONSTRUCTION** - (6 x26 IWRC) Available in 3/8", 7/16", 1/2" & 5/8" sizes in any length with Alloy Straight, Swivel or Self-Locking Hook
- **STAINLESS STEEL DUPLEX SLEEVE** - Precision cast internal hour glass shape maximizes sleeve to wire rope contact and cross sectional fill. Lip covers sharp wires in tail.

Working Load Limits - (3.55:1) Design Factor as per ASME/ASTM B30.5, formerly SAEJ959

Size/Description	WLL	Minimum Break Strength
3/8" Super Swaged	5,700 lbs.	20,400 lbs.
7/16" Super Swaged	7,600 lbs.	27,200 lbs.
1/2" Super Swaged	9,800 lbs.	34,800 lbs.
5/8" Super Swaged	15,200 lbs.	54,000 lbs.



**STRONGER & MORE DURABLE THAN STANDARD WINCH LINES OF THE SAME DIAMETER!**



**IN STOCK & READY TO SHIP** B/A Products Co. Sells Through Distribution Only

**WWW.BAPROD.COM**

© 2017 B/A Products Co. 12/17