

20CS

AHEAD OF THE PACK



NRC 
NRC-INDUSTRIES.COM

OUTREACH. OUTLAST.



GO AHEAD

t o w a w a y



Feeling like you can't find the perfect truck for smaller jobs? Not looking to compromise performance for size? Then you have to take a look at the impressive 20CS! Now offered with a rustproof composite body, this stylish 20-ton machine is ideal to tow tractors and heavy trucks and for recovery in urban areas.

Great return on investment: This affordable, light and dependable unit has a very low operating cost. Light, compact, and easy to maneuver, the 20CS Composite Slider has superior recovery capabilities that outclass other competing 20-ton units.

Great performance: The Slider System provides this unit with recovery capabilities and flexibility that are simply unmatched by others in its category. Match it with a NRC detachable tag axle and tow heavier units at a fraction of the cost, while flying over scales!

More fun: Conveniently located controls, easy access lockers and a new, interference-free, quick-latching detachable underlift turns every jobsite into a playground.



www.nrc-industries.com
Tel: 450 379-5796

WRECKER SPECIFICATION

Capacity: 20 Tons
Working hydraulic pressure 3000 PSI
Composite body 102" wide (including fenders)
140" CA (from cab to center of rear axle)

BOOM SPECIFICATIONS

Two stage boom: Standard
Boom structural rating fully retracted: 40,000 lbs @35°
Boom structural rating fully extended: 15,000 lbs @55°
Reach past tailgate fully extended : 147"
Maximum Boom working height : 256"
Boom range of elevation: 55°
360° sheave head

WINCHES & STEEL WIRE ROPE

Dual 20,000 lbs planetary winches
Wire rope: 5/8" x 200"
Air tensioners
Air free spools
Optional: 2 speed winches

UNDERLIFT SPECIFICATIONS

BASIC FORKS - 4 SETS - ALL UNDERLIFTS

- * 1 x Standard Bracket Set
- * 1 x Swivel Receivers Set
- * 1 x Back Axle Forks Set
- * 2 x Chain forks

HD -3

- * Reach (from tailboard) fully retracted : 68" <1727 mm>
- * Reach (from tailboard) fully extended : 99.5" <2838 mm>
- * Structural rating fully retracted : 35,000 lbs <16,000 kg>
- * Structural rating fully extended : 15,000 lbs <6,800 kg>

HD-3 (Euro)

- * Reach (from tailboard) fully retracted : 74.6" <1895 mm>
- * Reach (from tailboard) fully extended : 144.5" <3670 mm>
- * Structural rating fully retracted : 35,000 lbs <16,000 kg>
- * Structural rating fully extended : 16,000 lbs <7250 kg>

DISTRIBUTOR:



PM Industries Ltd.
1785 Mills Road, North Saanich
1-855-656-1689
sales@pmindustries.ca