

40CS

THE BEST OF BOTH WORLDS



NRC 
NRC-INDUSTRIES.COM

OUTREACH. OUTLAST.



GO AHEAD

t o w a w a y



Want a piece of equipment you can rely on?

A strong ally that will provide you with the peace of mind that **the job will be done in time**, no matter what circumstances you're dealing with?

Then think the **40CS!**

ALL-IN-ONE MARVEL: Forced to choose between towing and recovery? Make no compromise and get the most out of both! Featuring the Slider System, the unbreakable and perfectly balanced 40CS will allow you to focus on the job itself, not on the equipment.

ADAPTABLE: Its optional 3-stage boom can be adapted, transformed, and slid out to provide you with more reach - and more possibilities.

No wonder this truck is taking on superior class competitors!

NRC

www.nrc-industries.com
Tel: 450 379-5796

WRECKER SPECIFICATIONS

Capacity: 40 Tons
Working hydraulic pressure: 3000 PSI
Composite body 100" wide (including fenders)
183" C.A. (cab to center of rearmost axle)
CA for Tri-axle body: 200" (cab to center of rearmost axle)

BOOM SPECIFICATIONS

Two stage boom: Standard
Three stage boom: Option
«V» shape boom: Standard
Boom structural rating fully retracted: 80,000 lbs
Boom structural rating fully extended (2 stage): 30,000 lbs
Boom structural rating fully extended (3 stage): 15,000 lbs
Reach past tailgate (3rd stage) : 28'1"
Maximum boom working height (3rd stage) : 40'4"
Boom range of elevation: 60°
360° sheave head

WINCHES AND CABLES

Winch capacity (each): 40,000 lbs
Winch type: planetary
Wire rope: 3/4" x 200'
Air tensioners
Air free spool

UNDERLIFT SPECIFICATIONS

HD
* Reach fully retracted : 70"
* Reach fully extended : 108"
* Structural rating fully retracted : 35,000lbs
* Structural rating fully extended : 15,000lbs

SHD
* Reach fully retracted : 82"
* Reach fully extended : 131"
* Structural rating fully retracted : 50,000lbs
* Structural rating fully extended : 20,000lbs

SSH-4
* Reach fully retracted : 72"
* Reach fully extended : 145"
* Structural rating fully retracted : 70,000lbs
* Structural rating fully extended : 23,000lbs

LSHD-4
* Reach fully retracted : 82"
* Reach fully extended : 170"
* Structural rating fully retracted : 60,000lbs
* Structural rating fully extended : 20,000lbs

SSH-3 (Euro)
* Reach fully retracted : 81"
* Reach fully extended : 131"
* Structural rating fully retracted : 60,000lbs
* Structural rating fully extended : 25,000lbs

LSHD-3 (Euro)
* Reach fully retracted : 81"
* Reach fully extended : 144"
* Structural rating fully retracted : 50,000lbs
* Structural rating fully extended : 20,000lbs
*ALL MEASURES ARE FROM PIVOT POINT TO END OF T-BAR.

DISTRIBUTOR:



PM Industries Ltd.
1785 Mills Road, North Saanich
1-855-656-1689
sales@pmindustries.ca