



**50CS**

SEIZE MORE OPPORTUNITIES

**NRC**   
NRC-INDUSTRIES.COM

**OUTREACH. OUTLAST.**





# GO AHEAD

t o w a w a y



Looking for more reach and more power for all your towing and recovery needs?

Get the job done right every time using NRC's **BIG AND BOLD 50CS.**

**GREAT PERFORMANCE:** Perfect for the toughest recovery jobs, the 50CS has a longer and stronger boom for more lifting power and increased reach. Take advantage of the slider system to get the job done without compromising on towing capacity.

**INCREASE SAFETY:** Reliable and resistant, this 50-Ton titan means expanded business. And when NRC says 50 tons, it really means 50 tons! What you see is what you'll get. No bad surprises... just guaranteed success.

**GO IN STRONG** with the 50CS. Choose the most powerful equipment in its category!



[www.nrc-industries.com](http://www.nrc-industries.com)

Tel: 450 379-5796

**DISTRIBUTOR:**



PM Industries Ltd.  
1785 Mills Road, North Saanich  
1-855-656-1689  
[sales@pmindustries.ca](mailto:sales@pmindustries.ca)

## WRECKER SPECIFICATIONS

Capacity: 50 Tons  
Working hydraulic pressure: 3000 PSI  
Composite body 100" wide (including fenders)  
183" C.A. (cab to center of rearmost axle)  
CA for Tri-axle body: 200" (cab to center of rearmost axle)

## BOOM SPECIFICATIONS

Two stage boom: Standard  
Three stage boom: Option  
«V» shape boom: Standard  
Boom structural rating fully retracted: 100,000 lbs  
Boom structural rating fully extended (2 stage): 40,000 lbs  
Boom structural rating fully extended (3 stage): 20,000 lbs  
Reach past tailgate (3rd stage) : 281"  
Maximum boom working height (3rd stage) : 411"  
Boom range of elevation: 60°  
360° sheave head

## WINCHES AND CABLES

Winch capacity (each): 50,000 lbs  
Winch type: planetary  
Wire rope: 7/8" x 200'  
Air tensioners  
Air free spool

## UNDERLIFT SPECIFICATIONS

HD  
\* Reach fully retracted : 70"  
\* Reach fully extended : 108"  
\* Structural rating fully retracted : 35,000lbs  
\* Structural rating fully extended : 15,000lbs

SHD  
\* Reach fully retracted : 82"  
\* Reach fully extended : 131"  
\* Structural rating fully retracted : 50,000lbs  
\* Structural rating fully extended : 20,000lbs

SSH-4  
\* Reach fully retracted : 72"  
\* Reach fully extended : 145"  
\* Structural rating fully retracted : 70,000lbs  
\* Structural rating fully extended : 23,000lbs

LSHD-4  
\* Reach fully retracted : 82"  
\* Reach fully extended : 170"  
\* Structural rating fully retracted : 60,000lbs  
\* Structural rating fully extended : 20,000lbs

SSH-3 (Euro)  
\* Reach fully retracted : 81"  
\* Reach fully extended : 131"  
\* Structural rating fully retracted : 60,000lbs  
\* Structural rating fully extended : 25,000lbs

LSHD-3 (Euro)  
\* Reach fully retracted : 81"  
\* Reach fully extended : 144"  
\* Structural rating fully retracted : 50,000lbs  
\* Structural rating fully extended : 20,000lbs  
\*ALL MEASURES ARE FROM PIVOT POINT TO END OF T-BAR.