



**60/80SR**

BREAK NEW GROUND

**NRC**   
NRC-INDUSTRIES.COM

**OUTREACH. OUTLAST.**



# GO AHEAD

t o w a w a y



Want to be the ultra heavy-duty recovery specialist? To make a stand where others can't? Not even the sky's the limit and you can now do any recovery job with **THE ONE AND ONLY 60/80SR!**

Designed to **SIMPLIFY EVEN THE MOST COMPLICATED RECOVERIES**, the 60/80SR features an oversized version of the proven Slider System, combined with a gigantic V-shaped boom and 60,000 lb planetary winches.

Now you get **POWER AND EFFICACY** that will allow you to work more recovery sites than any other competitor.

One step above all other rotators, the power and technology of this work beast will let you **REACH, LIFT, AND PULL ANYTHING IMAGINABLE** including what you once thought was impossible!

**ULTIMATE RECOVERY PERFORMANCE  
MORE BOOM POWER FOR YOUR SAFETY.**



www.nrc-industries.com  
Tel: 450 379-5796

**DISTRIBUTOR:**



PM Industries Ltd.  
1785 Mills Road, North Saanich  
1-855-656-1689  
sales@pmindustries.ca

## WRECKER SPECIFICATIONS

80 Ton hydraulic wrecker  
60 Ton Safe lifting capacity (25% security factor)  
Heavy duty body 100" wide  
Minimum CA for tandem and tri-axle body: 269"  
(from cab to center of rearmost axle)

## BOOM SPECIFICATIONS

Two stage boom: standard  
Three stage boom: option  
«V» shape boom  
Approximative weight : 50,000lbs  
Approximative weight with Axle-lift: 52,000lbs  
Boom basic structural rating fully retracted : 160,000lbs  
Boom basic structural rating fully extended : 50,000lbs  
Reach past tailgate (3rd stage) : 485"  
Maximum Boom working height (3rd stage) : 664"  
Range of elevation : 0° - 73°  
360 (degree) sheave head

## WINCHES AND CABLES

Dual 60,000lbs planetary two speed winches  
7/8" x 200' steel cable on each drum  
Air clutch release on winches  
Air tensioners  
Opt: 2 planetary 20,000 lbs aux. winches under boom

## UNDERLIFT SPECIFICATIONS

HD  
\* Reach fully retracted : 70"  
\* Reach fully extended : 108"  
\* Structural rating fully retracted : 35,000lbs  
\* Structural rating fully extended : 15,000lbs

SHD  
\* Reach fully retracted : 82"  
\* Reach fully extended : 131"  
\* Structural rating fully retracted : 50,000lbs  
\* Structural rating fully extended : 20,000lbs

SSH-4  
\* Reach fully retracted : 72"  
\* Reach fully extended : 145"  
\* Structural rating fully retracted : 70,000lbs  
\* Structural rating fully extended : 23,000lbs

LSHD-4  
\* Reach fully retracted : 82"  
\* Reach fully extended : 170"  
\* Structural rating fully retracted : 60,000lbs  
\* Structural rating fully extended : 20,000lbs

SSH-3 (Euro)  
\* Reach fully retracted : 81"  
\* Reach fully extended : 131"  
\* Structural rating fully retracted : 60,000lbs  
\* Structural rating fully extended : 25,000lbs

LSHD-3 (Euro)  
\* Reach fully retracted : 81"  
\* Reach fully extended : 144"  
\* Structural rating fully retracted : 50,000lbs  
\* Structural rating fully extended : 20,000lbs

\*ALL MEASURES ARE FROM PIVOT POINT TO END OF T-BAR.