

QUICK SWAP

BE FREE. BE FAST.
MAKE MORE MONEY.



NRC 
NRC-INDUSTRIES.COM

OUTREACH. OUTLAST.



GO AHEAD

t o w a w a y



All you need is a destination. Something to tow. Let the lightweight and power of the Quickswap do the trick. Be free, be fast, make more money.

As the best-selling equipment in its category, the Quickswap is the most efficient and versatile detachable unit available to date.

SEIZE THE OPPORTUNITY: Take advantage of the detachable design at every opportunity to push your limits during high seasons,...and adapt during slower periods. At anytime, add a winch and use it as a supporting recovery unit

MAKE MORE MONEY: Cost-effective, this versatile lightweight unit will save you big on fuel and on maintenance. Great return on investment.

PEACE OF MIND: Its superior towing capacity and lightweight will light up your day when you hit the scales.!

BASIC SPECIFICATIONS

Detachable from tractor in minutes
 Dual cylinders for underlift elevation
 Hydraulic underlift (stinger) extension
 Hydraulic actuated tilt boom
 Hydraulic fold
 Front receiver (permanently mounted on chassis)
 Removable front stands
 Manual controls
 Safety chain pockets
 Aluminum fenders
 Federal standard #108 compliant light group
 Fork storage and holders
 Tie-down chains
 Epoxy primer paint

CHASSIS REQUIREMENTS

Heavy Duty Quickswap
 Minimum wheelbase : 250"
 Double frame recommended

Super Heavy Duty Quickswap
 Minimum wheelbase : 275"
 Double frame recommended

UNDERLIFT SPECIFICATIONS

HD
 * Reach fully retracted : 70"
 * Reach fully extended : 108"
 * Structural rating fully retracted : 35,000lbs
 * Structural rating fully extended : 15,000lbs

SHD
 * Reach fully retracted : 82"
 * Reach fully extended : 131"
 * Structural rating fully retracted : 50,000lbs
 * Structural rating fully extended : 20,000lbs

SSH-4
 * Reach fully retracted : 72"
 * Reach fully extended : 145"
 * Structural rating fully retracted : 70,000lbs
 * Structural rating fully extended : 23,000lbs

LSD-4
 * Reach fully retracted : 82"
 * Reach fully extended : 170"
 * Structural rating fully retracted : 60,000lbs
 * Structural rating fully extended : 20,000lbs

SSH-3 (Euro)
 * Reach fully retracted : 81"
 * Reach fully extended : 131"
 * Structural rating fully retracted : 60,000lbs
 * Structural rating fully extended : 25,000lbs

LSD-3 (Euro)
 * Reach fully retracted : 81"
 * Reach fully extended : 144"
 * Structural rating fully retracted : 50,000lbs
 * Structural rating fully extended : 20,000lbs

*ALL MEASURES ARE FROM PIVOT POINT TO END OF T-BAR.



www.nrc-industries.com
 Tel: 450 379-5796

DISTRIBUTOR:



PM Industries Ltd.
 1785 Mills Road, North Saanich
 1-855-656-1689
 sales@pmindustries.ca