



QUICK SWAP

WITH TAG AXLE

NRC 
NRC-INDUSTRIES.COM

OUTREACH. OUTLAST.



STAND OUT!

The Quickswap with Tag Axle is a class of its own. It features a unique lightweight yet powerful detachable design to let you do things differently, stand out, and be successful where others fail.

SAFETY FIRST: When everything goes so fast, braking power is crucial. The additional set of brakes will make you stay in control and stop whenever you have to.

DON'T MISS A CALL: Detachable design will help you deliver during the high season and be flexible when business goes back to normal. Add a winch and use it as a supporting recovery unit.

DO MORE: Put the tag axle down and tow what others can't. Lift it up and save on fuel. Increase your revenues. Lower your costs. Quickly see the return on investment.

DON'T WORRY, RIDE HAPPY:

Experience the outstanding driveability thanks to the adjustable air ride suspension. Haul heavier vehicles and cross the scale with a big smile across your face.



www.nrc-industries.com
Tel: 450 379-5796

DISTRIBUTOR:



PM Industries Ltd.
1785 Mills Road, North Saanich
1-855-656-1689
sales@pmindustries.ca

BASIC SPECIFICATIONS

- Detachable from tractor in minutes
- Single cylinders for underlift elevation
- Hydraulic underlift (stinger) extension
- Hydraulic actuated tilt boom
- Hydraulic fold
- 17,000lbs [7 700kg] tag axle
- Liftable air ride suspension
- Air brakes
- 4 x 215/70R17.5 radial tires w/ dual steel wheels
- Load control adjustment w/ air pressure dial
- Front and rear receivers (permanently mounted on chassis)
- Removable front stands
- Manual controls
- Safety chain pockets
- Aluminum fenders
- Federal standard #108 compliant light group
- Fork storage and holders
- Tie-down chains
- Epoxy primer paint

CHASSIS REQUIREMENTS

Heavy Duty Quickswap
Minimum wheelbase : 250"
Double frame recommended

Super Heavy Duty Quickswap
Minimum wheelbase : 275"
Double frame recommended

UNDERLIFT SPECIFICATIONS

HD
* Reach fully retracted : 70"
* Reach fully extended : 108"
* Structural rating fully retracted : 35,000lbs
* Structural rating fully extended : 15,000lbs

SHD
* Reach fully retracted : 82"
* Reach fully extended : 131"
* Structural rating fully retracted : 50,000lbs
* Structural rating fully extended : 20,000lbs

SSH-4
* Reach fully retracted : 72"
* Reach fully extended : 145"
* Structural rating fully retracted : 70,000lbs
* Structural rating fully extended : 23,000lbs

LSHD-4
* Reach fully retracted : 82"
* Reach fully extended : 170"
* Structural rating fully retracted : 60,000lbs
* Structural rating fully extended : 20,000lbs

SSH-3 (Euro)
* Reach fully retracted : 81"
* Reach fully extended : 131"
* Structural rating fully retracted : 60,000lbs
* Structural rating fully extended : 25,000lbs

LSHD-3 (Euro)
* Reach fully retracted : 81"
* Reach fully extended : 144"
* Structural rating fully retracted : 50,000lbs
* Structural rating fully extended : 20,000lbs

*ALL MEASURES ARE FROM PIVOT POINT TO END OF T-BAR.