

ROADRUNNER

BIG AND BOLD



NRC 
NRC-INDUSTRIES.COM

OUTREACH. OUTLAST.



GO AHEAD

t o w a w a y



MAKE HEADS SWIVEL! Hook up the heaviest loads and enjoy the ride.

This permanent mount towing equipment uses powerful and lightweight Quicksnap technology, so you never miss an opportunity. It also shares its composite body with the CS-Series, so you take advantage of the huge storage compartments, while making sure you don't go unnoticed.

MAKE MORE MONEY: Cost-effective and lightweight, this workhorse will save you on fuel and on maintenance, while providing you with a large payload. Excellent return on investment, guaranteed!

PEACE OF MIND: Superior towing capacity and lightweight versatility will put a smile on your dial when you weigh in at the scales.

NIFTY VERSATILITY! Add a winch and jack legs to provide this towing unit with advanced recovery capabilities. No matter how far you go, you'll be ready for some serious action!

BASIC SPECIFICATIONS

- Single cylinders for underlift elevation
- Hydraulic underlift (stinger) extension
- Hydraulic actuated tilt boom
- Hydraulic fold
- Enclosed manual hydraulic controls with lighting
- Emergency stop switches
- Hydraulic pressure gauges
- Rear mounted recovery anchors
- Safety chains (2 - 1/2" x 13' grade 8)
- Mud flaps
- Federal standard #108 compliant light group
- LED Lights
- B marker lights per side
- Chain locker
- Extruded aluminum modular sliding tracks in toolboxes
- Modular Fork and accessories holders
- Air & Electrical hookups
- Tailboard mounted D-rings
- Optional: Hydraulic stabilizers (jack legs)

WINCHES AND WIRE ROPE

- Optional: 20,000 lb planetary winch
- Optional: 25,000 lb worm gear winch
- Cable 5/8" x 200'
- Air tensioner

UNDERLIFT SPECIFICATIONS

- HD**
- * Reach fully retracted : 70"
 - * Reach fully extended : 108"
 - * Structural rating fully retracted : 35,000lbs
 - * Structural rating fully extended : 15,000lbs

- SHD**
- * Reach fully retracted : 82"
 - * Reach fully extended : 131"
 - * Structural rating fully retracted : 50,000lbs
 - * Structural rating fully extended : 20,000lbs

- SSH-4**
- * Reach fully retracted : 72"
 - * Reach fully extended : 145"
 - * Structural rating fully retracted : 70,000lbs
 - * Structural rating fully extended : 23,000lbs

- LSHD-4**
- * Reach fully retracted : 82"
 - * Reach fully extended : 170"
 - * Structural rating fully retracted : 60,000lbs
 - * Structural rating fully extended : 20,000lbs

- SSH-3 (Euro)**
- * Reach fully retracted : 81"
 - * Reach fully extended : 131"
 - * Structural rating fully retracted : 60,000lbs
 - * Structural rating fully extended : 25,000lbs

- LSHD-3 (Euro)**
- * Reach fully retracted : 81"
 - * Reach fully extended : 144"
 - * Structural rating fully retracted : 50,000lbs
 - * Structural rating fully extended : 20,000lbs

*ALL MEASURES ARE FROM PIVOT POINT TO END OF T-BAR.



www.nrc-industries.com
Tel: 450 379-5796

DISTRIBUTOR:



PM Industries Ltd.
1785 Mills Road, North Saanich
1-855-656-1689
sales@pmindustries.ca